





CAT CANYON OIL FIELD Sisquoc Area and West Area










CAT CANYON OIL FIELD

GATO RIDGE AREA

TYPICAL ELECTRIC SERIES FORMATION LOG SIB ELECTRIC -PLIOCENE SISQUOC MONTEREY

TINAQUAIC AREA



OLIVERA CANYON AREA

SERIES	M EI	MATION MBER ND ONE		YPICAL ECTRIC LOG
	FOXE		~-\{	- \\
PLIOCENE	SISQL	SIB	Jumes of the state	- \$1500
MIOCENE	MONTEREY	BENTONITIC BROWN AND CHERTY ARENACEOUS	m	2000 2500 2500 2500 2500 2500 2500 2500
	RINC	ON	MAN	77500 - 4500

Santa Barbara County

LOCATION: 8 miles southeast of Santa Maria

TYPE OF TRAP: See areas ELEVATION: 700 - 1,400

DISCOVERY DATA

					prode	daily uction Gas	Date of
Zone	Present operator and well name	Original operator and well name	Sec. T. & R.	B&M	(bbl)	(Mcf)	completion
Sisquoc	Union Oil Co. of Calif. "Palmer Stendel" (Old) 1	Palmer Union Oil Co. 1	26 9N 33W	SB	150	N.A.	1908
						()	1

Remarks:

DEEPEST WELL DATA

	200	Date			Depth	At total depth	
Present operator and well name	Original operator and well name			8 & M		Strata	Age
Continetal Oil Co. "McNee" 4	Union Oil Co. of Calif. "McNee" 4	Jul 1945	20 9N 32W	SB	9,001	Rincon	early Mio

PRODUCING ZONES (See areas)

RODUCING ZONES	(see areas)						
	Average depth	Average net thickness	Geo	logic	Oil gravity (*API) or	Salinity of zone water	Class BOPE
Zone	(feet)	(feet)	Age	Formation	Gas (btu)	gr/gal	required
			1				
	1		1		1 1		
	1 1				1 1		
	1				1 1		
					1 1		
	1 0				1	1	

PRODUCTION DATA (Jan. 1, 1974)

1973 Production			1973 Proved	1973 Average number	Cumulative production		Peak oil production		Total num	Total number of wells	
Oil (bbl)	Net gas (Mcf)	Water (bbl)	acreage	producing wells	Oil (bbl)	Gas (Mcf)	Barrels	Year	Drilled	Completed	acreage
6,832,620	3,601,914	33,499,949	7,400	634	208,900,427	105,519,748	8,373,328	1953	1,334	1,174	8,160

STIMULATION DATA (Jan. 1, 1974) (See areas)

Type of project	Date started	Cumulative injection - Water, bbl; Gas, Mcf; Steam, bbl (water equivalent)	Maximum number of wells used for injection

SPACING ACT: See areas

BASE OF FRESH WATER: See areas

CURRENT CASING PROGRAM: See areas

METHOD OF WASTE DISPOSAL: See areas

REMARKS: Effective January 1, 1972, the Four Deer area of Cat Canyon oil field was classified as a separate field.

REFERENCES: Prutzman, P.W., Petroleum in Southern California: Calif. State Mining Bureau Bull. 63 (1912).
Woodring, N.P., and M.N. Bramlette, Geology and Paleontology of the Santa Maria District, California: U.S. Geol. Survey Prof. Paper 222, p. 120 (1950).

CAT CANYON OIL FIELD

CENTRAL AREA

Santa Barbara County

LOCATION: See map sheet of Cat Canyon Oil Field

TYPE OF TRAP: Sand pinchout on homocline

ELEVATION: 1,000 DISCOVERY DATA

			A		Initial daily production		Date of
Zone	Present operator and well name	Original operator and well name	Sec. T. & R.	B & M	(ppl)	Gas (Mcf)	completion
Sisquoc	Getty Oil Co. "Los Alamos" 32	Pacific Western Oil Corp. "Los Alamos" 32	6 8N 32W	SB	184	8	May 1956

Remarks:

DEEPEST WELL DATA

		Date			Depth	At total depth	
Present operator and well name	Original operator and well name			3 & M	(feet)	Strata	Age
Getty Oil Co. "Los Alamos" 32	Pacific Western Oil Corp. "Los Alamos" 32	Feb 1956	6 8N 32W	SB	5,210	Monterey	Miocene

PRODUCING ZONES

	Average depth	Average net			Average net Geologic Oil gravity (*API) or		Oil gravity	Salinity of zone water	Class BOPE
Zone	(feet)	(feet)	Age	Formation	Gas (btu)	gr/gal	required		
Sisquoc	2,800	45	Pliocene	Sisquoc	13	450	11		

PRODUCTION DATA (Jan. 1, 1974)

1973 Production			1973 Proved	1973 Average number	Cumulative production		Peak oil production Total number		Total number of wells		Maximum
011 (bb1)	Net gas (Mcf)	Water (bbl)	acreage	producing wells	Oil (bbl)	Gas (Mcf)	Barrels	Year	Drilled	Completed	acreage
559,826	58,321	1,046,398	590	47	N.A.	N.A.	N.A.	N.A.	84	71	710

STIMULATION DATA (Jan. 1, 1974)

Type of project	Date started	Cumulative injection - Water, bbl; Gas, Mcf; Steam, bbl (water equivalent)	Maximum number of wells used for injection
Water flood	1964	18,002,456	9
Cyclic steam	1963	1,180,231	15
Fire flood	1965	41,322	1

SPACING ACT: Applies

BASE OF FRESH WATER: 850

CURRENT CASING PROGRAM: 10 3/4" cem. 275; 7" cem. above zone and across base of fresh-water sands; 5 1/2" liner landed through zone.

METHOD OF WASTE DISPOSAL: Waste water is used in the water-flood project.

REMARKS: This area was formerly considered to be part of the West area.

REFERENCES: Bailey, Wm., C., Operations in District No. 3: Calif. Div. of Oil and Gas, Summary of Operations--Calif. Oil Fields, Vol. 42, No. 2, p. 93 (1956).

Santa Barbara County

EAST AREA

LOCATION: See map sheet of Cat Canyon Oil Field

TYPE OF TRAP: Faulted homocline; lenticular sands.

ELEVATION: 900

DISCOVERY DATA

						daily uction		
Zone	Present operator and well name	Original operator and well name	Sec. T. & R.	B & M	Oil (bbl)	Gas (Mcf)	Date of completion	
Sisquoc Brooks Monterey	Getty Oil Co. "G.W.P." 44A Robert G. Russell & Son "Field Fee" 1 Continental Oil Co. "Forter" 1-C	Slick-Moorman Production Co. 44A Brooks Oil Co. 1 Slick-Moorman Production Co. "Palmer Stendel" 1-C	24 9N 33W 31 9N 32W 24 9N 33W	SB SB SB	25 150 *7	0	Jun 1953 1909 Oct 1953	

Remarks: * Includes some oil produced from 40' of basal Sisquoc sand.

DEEPEST WELL DATA

40		Date			Deoth	At total	depth
Present operator and well name	Original operator and well name	started	Sec. T. & R.	3 & M		Strata	Age
Husky 0il Co. of Delaware "Victory" 20	Palmer Union Oil Co. "Stendel" 20	Jul 1928	30 9N 32W	SB	7,200	Knoxville	Jurassic

PRODUCING ZONES

	Average depth	Average net thickness		Geologic	Oil gravity (*API) or	Salinity of	Class BOPE
Zone	(feet)	(feet)	Age	Formation	Gas (btu)	zone water gr/gal	required
Sisquoc Brooks	3,000 2,100	250 200 500	Pliocene late Miocene Miocene	Sisquoc Monterey Monterey	18 10 6	N.A. 425 330	I I II
Monterey 3,0	3,000	300	, accent	, and the second		330	
	1 1				1		

PRODUCTION DATA (Jan. 1, 1974)

	1973 Production		1973 Proved	1973 Average number	Cumulative p	roduction	Peak oil produ	uction	Total num	ber of wells	Maximum
Oil (bbl)	Net gas (Mcf)	Water (bbl)	acreage	producing wells	OII (bbI)	Gas (Mcf)	Barrels	Year	Drilled	Completed	acreage
752,180	24,220	1,083,280	1,120	111	N.A.	N.A.	N.A.	N.A.	230	199	1,280

STIMULATION DATA (Jan. 1, 1974)

Type of project	Date started	Cumulative injection - Water, bbl; Gas, Mcf; Steam, bbl (water equivalent)	Maximum number of wells used for injection
Steam flood	1966	3,971,777	9
Cyclic steam	1964	2,672,691	77

SPACING ACT: Does not apply

BASE OF FRESH WATER: 1,000

CURRENT CASING PROGRAM: 10 3/4" cem. 300; 7" cem. above zone and across base of fresh-water sands; 5 1/2" liner landed through zone.

METHOD OF WASTE DISPOSAL: Waste water is injected into disposal wells.

REMARKS: East area data includes the Slick-Moorman area.

REFERENCES: Bailey, Wm. C., Operations in District No. 3: Calif. Div. of Oil and Gas, Summary of Operations--Calif. Oil Fields, Vol. 39, No. 2 (1953).

Cross, R.K., East Cat Canyon Area of the Cat Canyon Oil Field: Calif. State Div. of Mines Bull. 118, p. 435 (1940).

Prutzman, P.W., Petroleum in Southern California: Calif. State Mining Bureau Bull. 63, p. 379 (1912).

Woodring, W.P., and M.N. Bramlette, Geology and Paleontology of the Santa Maria District, California: U.S. Geol. Survey Prof. Paper 222, p. 121 (1950).

CAT CANYON OIL FIELD

Santa Barbara County

GATO RIDGE AREA

LOCATION: See map sheet of Cat Canyon Oil Field

TYPE OF TRAP: Faulted anticline

ELEVATION: 1,400

DISCOVERY DATA

						al daily luction	
Zone	Present operator and well name	Original operator and well name	Sec. T. & R.	B & M	(bbl)	Gas (Mcf)	Date of completion
Sisquoc	Union Oil Co. of Calif. "Union-Continental" 1	O.C. Field Gasoline Corp. "Continental" 1	4 8N 32W	SB SB	580	N.A.	Mar 1937 Jan 1915
Buff and Brown	Pinal Dome Corp. No. T-2	Same as present	15 04 324	36	30		Jan 1915

Remarks:

DEEPEST WELL DATA

		Date			Depth	At tota	il depth
Present operator and well name	Original operator and well name	started	Sec. T. & R.	3 & M		Strata	Age
un Oil Co. "Tognazzini" 1	Barnsdall Oil Co. of Calif. "Tognazzini" 1	Apr 1930	9 8N 32W	SB	6,510	Monterey	Miocene

PRODUCING ZONES

	Average depth	Average net thickness	Geologic		Oil gravity (*API) or	Satinity of zone water	Class BOPE
Zone	(feet)	(feet)	Age	Formation	Gas (btu)	gr/gal	required
Sisquoc Buff and Brown	2,210 3,800	200 300	early Pliocene Miocene	Sisquoc Monterey	14 13	N.A. 330	II

PRODUCTION DATA (Jan. 1, 1974)

	1973 Production		1973 Proved	1973 Average number	Cumulative pr	roduction	Peak oil produ	ection	Total num	iber of wells	Maximum
Oil (bb1)	Net gas (Mcf)	Water (bbl)	acreage	producing wells	O11 (bb1)	Gas (Mcf)	Barrels	Year	Dritted	Completed	acreage
475,885	688,958	1,504,465	690	66	N.A.	N.A.	N.A.	N.A.	114	94	740

STIMULATION DATA (Jan. 1, 1974)

Type of project	Date started	Cumulative injection - Water, bbl; Gas, Mcf; Steam, bbl (water equivalent)	Maximum number of wells used for injection

SPACING ACT: Does not apply

BASE OF FRESH WATER: None

CURRENT CASING PROGRAM: 10 3/4" cem. 300; 7" cem. above zone; 5 1/2" liner landed through zone.

METHOD OF WASTE DISPOSAL: Waste water is injected into Monterey zone disposal wells.

REMARKS:

REFERENCES: Cross, R.K., Gato Ridge Area of Cat Canyon Oil Field: State Div. of Mines, Bull. 118, p. 438 (1940).
Dolman, S.G., Operations in District No. 3: Calif. Div. of Oil and Gas, Summary of Operations--Calif. Oil Fields, Vol. 17, No. 3, p. 34 (1931).
Woodring, W.P., and M.N. Bramlette, Geology and Paleontology of the Santa Maria District, California: U.S. Geol. Survey Prof. Paper 222, p. 121 (1950).

OLIVERA CANYON AREA

CAT CANYON OIL FIELD Santa Barbara County

LOCATION: See map sheet of Cat Canyon Oil Field

TYPE OF TRAP: Anticline

ELEVATION: 800

DISCOVERY DATA

						i daily uction	
Zone	Present operator and well name	Original operator and well name	Sec. T. & R.	B&W	(1dd)	Gas (Mcf)	Date of completion
Cherty - Bentonitic	Continental Oil Co. "McNee" 2	Union Oil Co. of Calif. "McNee" 2	20 9N 32W	SB	37	N.A.	Jun 1944
Buff and Brown	Same as above	Same as above	20 9N 32W	SB	*	N.A.	Jun 1944

Remarks: * Production commingled.

DEEPEST WELL DATA

		Date			Depth	At tot	al depth
Present operator and well name	Original operator and well name	started	Sec. T. & R.	3 % M		Strata	Age
Continental Oil Co. "McNee" 4	Union Oil Co. of Calif. "McNee" 4	Jul 1945	20 9N 32W	SB	9,001	Rincon	early Mio

PRODUCING ZONES

	Average depth	Average net thickness		Geologic	Oil gravity (*API) or	Salinity of	Class BOPE
Zone	(feet)	(feet)	Age	Formation	Gas (btu)	zone water gr/gat	required
Cherty - Bentonitic Brown	3,000	1,200	Miocene	Monterey	10	700	11
Buff and Brown	4,000	300	Miocene	Monterey	10	700	II
			1			1	

PRODUCTION DATA (Jan. 1, 1974)

1973 Production		1973 1973 Cumulative pro		roduction	oduction Peak oil production		Total number of wells		Maximum proved		
Oil (bbl)	Net gas (Mcf)	Water (bbl)	acreage	producing wells	Oil (bbl)	Gas (Mcf)	Barrels	Year	Dritled	Completed	acreage
223,648	0	459,221	200	15	4,578,523	0	369,422	1953	37	23	210

STIMULATION DATA (Jan. 1, 1974)

Type of project	Date started	Cumulative injection - Water, bbl; Gas, Mcf; Steam, bbl (water equivalent)	Maximum number of wells used for injection

SPACING ACT: Applies

BASE OF FRESH WATER: 600

CURRENT CASING PROGRAM: 13 3/8" cem. 720; 8 5/8" combination string landed through zone and cemented through ports above zone.

METHOD OF WASTE DISPOSAL: Waste water is injected into water-disposal wells.

REMARKS:

REFERENCES: Dolman, S.G., Operations in District No. 3: Calif. Div. of Oil and Gas, Summary of Operations--Calif. Oil Fields, Vol. 30, No. 2, p. 43 (1944).

SISQUOC AREA

LOCATION: See map sheet of Cat Canyon Oil Field

TYPE OF TRAP: Permeability barrier on west flank of anticline

ELEVATION: 700

DISCOVERY DATA

						daily uction	1
Zone	Present operator and well name	Original operator and well name	Sec. T. & R.	B & M	Oil (bbl)	Gas (Mr!)	Date of completion
Sisquoc	Husky Oil Co. of Del. "Goodwin" 1	Union Oil Co. of Calif. "Santa Maria Realty" 1	10 9N 33W	SB	69	0	Dec 1944
Thomas Monterey	Shell Oil Co. "Thomas" 88-X Husky Oil Co. of Del. "Goodwin" 1	M J M & M Oil Co. "Thomas" 88-X Union Oil Co. of Calif. "Santa Maria Realty" 1	15 9N 33W 10 9N 33W	SB SB	89	0	Nov 1954 Dec 1944

Remarks: * Production from Sisquoc and Monterey zones commingled.

DEEPEST WELL DATA

		Date			Depth	At tota	l depth
Present operator and well name	Original operator and well name	started	Sec. T. & R.	3 & M		Strata	Age
Shell Oil Co. "Lloyd et al" 7	Same	Mar 1971	15 9N 33W	SB	7,860	Monterey	Miocene

PRODUCING ZONES

	Average depth	Average net thickness		Geologic	Oil gravity (*API) or	Salinity of zone water	Class BOPE
Zone	(feet)	(feet)	Age	Formation	Gas (btu)	gr/gal	required
Sisquoc Thomas Monterey	2,750 4,900 4,000	500 70 500	Pliocene Miocene Miocene	Sisquoc Sisquoc Monterey	10 7 9	50 700 610	11 11

PRODUCTION DATA (Jan. 1, 1974)

1973 Production			Proved Average number		Cumulative production		Peak oil production		Total number of wells		Maximum	
Oil (bbl)	Net gas (Mcf)	Water (bbl)	acreage	producing wells	Oil (bbl)	Gas (Mcf)	Barrels	Year	Drilled	Completed	acreage	
3,305,917	396,492	3,472,015	1,970	231	N.A.	N.A.	N.A.	N.A.	401	374	2,190	

STIMULATION DATA (Jan. 1, 1974)

Type of project	Date started	Cumulative injection - Water, bbl; Gas, Mcf; Steam, bbl (water equivalent)	Maximum number of wells used for injection
Water flood	1963	1,404,573	2
Steam flood	1967	693,193	2
Cyclic steam	1963	10,675,132	289

SPACING ACT: Applies

BASE OF FRESH WATER: 2,000

CURRENT CASING PROGRAM: 10 3/4" cem. 60 or 9 5/8" cem. 400; 7" combination string landed through zone and cemented through ports above zone and across base of fresh-water sands; 7" cem. above zone to the surface; 5 1/2" liner hung through zone (Sisquoc).

METHOD OF WASTE DISPOSAL: Waste water is injected into disposal wells.

REMARKS. The Sisquoc area includes the Bradley Canyon area.

REFERENCES: Bailey, Wm. C., Operations in District No. 3: Calif. Div. of Oil and Gas, Summary of Operations--Calif. Oil Fields, Vol. 40, No. 2 (1954).

TINAQUAIC AREA

CAT CANYON OIL FIELD

Santa Barbara County

LOCATION: See map sheet of Cat Canyon Oil Field

TYPE OF TRAP: Anticline

ELEVATION: 1,020

DISCOVERY DATA

						l daily uction	
Zone	- Present operator and well name	Original operator and well name	Sec. T. & R.	B & M	(bbi)	Gas (Mcf)	Date of completion
Monterey	Continental Oil Co. "Wickenden" 1	Four-Five-Six Oil Co. "Wickenden" 1	34 9N 32W	SB	90	0	Feb 1945

Remarks

DEEPEST WELL DATA

		Date			Depth	At total	depth
Present operator and well name	Original operator and well name s		Sec. T. & R.	3 & M		Strata	Age
Continental Oil Co. "Wickenden" 5	Same	Jun 1973	33 9N 32W	SB	5,250	Monterey	Miocene

PRODUCING ZONES

		Geologic				Class BOPE
		Gas (btu)	zone water gr/gal	required		
2,020 - 3,180	1,200 - 3,200	Miocene	Monterey	6	N.A.	11
	2,020 -	2,020 - 1,200 -	2,020 - 1,200 - Miocene	2,020 - 1,200 - Miocene Monterey	2,020 - 1,200 - Miocene Monterey 6	2,020 - 1,200 - Miocene Monterey 6 N.A.

PRODUCTION DATA (Jan. 1, 1974)

	1973 Production	73 Production		1973 Average number	Cumulative production		Peak oil produ	uction	Total num	ber of wells	Maximum
Oil (bbl)	Net gas (Mcf)	Water (bb1)	Proved acreage	producing wells	OII (bb1)	Gas (Mcf)	Barrels	Year	Drilled	Completed	acreage
6,963	0	4,559	50	2	21,519	0	7,342	1948	7	3	50

STIMULATION DATA (Jan. 1, 1974)

Type of project	Date started	Cumulative injection - Water, bbl; Gas, Mcf; Steam, bbl (water equivalent)	Maximum number of wells used for injection

SPACING ACT: Applies

BASE OF FRESH WATER: 380 - 600

CURRENT CASING PROGRAM: 13 3/8" cem. 200; 8 5/8" combination string landed through zone and cemented through ports above zone and across base of freshwater sands; or 9 5/8" cem. 1,800; 7" liner landed through zone.

METHOD OF WASTE DISPOSAL: Water is transported to Olivera Canyon area for subsurface disposal.

REMARKS: No formal production reports were filed until July 1948. Cumulative production only includes oil that was reported since July 1948.

REFERENCES: Dolman, S.G., Operations in District No. 3: Calif. Div. of Oil and Gas, Summary of Operations -- Calif. Oil Fields, Vol. 31, No. 2 (1945).

WEST AREA

CAT CANYON OIL FIELD Santa Barbara County

LOCATION: See map sheet of Cat Canyon Oil Field

TYPE OF TRAP: Faulted anticline; sand pinchout

ELEVATION: 800 - 1,200

DISCOVERY DATA

				8 & M	Initial daily production		
Zone	Present operator and well name	Original operator and well name	Sec. T. & R.		Oil (bbi)	Gas (Mcf)	Date of completion
Sisquoc (S _{1b})	Union Oil Co. of Calif, "Palmer Stendel" (Old) 1	Palmer Union Oil Co. 1	26 9N 33W	SB	150	N.A.	1908
Alexander (Sg-S ₁₀) Los Flores (Cherty)	Standard Oil Co. of Calif. "Alexander" 164 Standard Oil Co. of Calif. "Los Flores" 1-1	Same as present Standard 0il Co. of Calif. "Los Flores Land and 0il Co. Standard" 1	21 9N 33W 27 9N 33W	SB SB	366 716	N.A.	Mar 1953 Aug 1938

Remarks: Indications of oil in the Monterey Formation were noted as early as August 1918 in Pan American Pet. Inv. Corp. well No. 15A (now Getty Oil Co. "Los Alamos" 15-A).

DEEPEST WELL DATA

		Date			Depth	At total depth	
Present operator and well name	Original operator and well name	started	Sec. T. & R.	3 & M		Strata	Age
nion Oil Co. of Calif. "Bell" 106	Same	Sep 1951	35 9N 33W	SB	7,460	Monterey	Miocene

PRODUCING ZONES

	Average depth	Average net thickness (feet)		Geologic	Oil gravity (*API) or	Salinity of	Class BOPE required
Zone	(feet)		Age	Formation	Gas (btu)	zone water gr/gal	
Sisquoc (S _{1b}) Alexander (S ₉ -S ₁₀)	2,800	600	Pliocene	Sisquoc	17	1,330	11
Alexander (S ₉ -S ₁₀) Los Flores (Cherty)	3,750 6,000	1,500	Pliocene Miocene	Sisquoc Monterey	23 15	1,200	11

PRODUCTION DATA (Ian. 1, 1974)

1973 Production		1973 Proved	1973 Average number	Cumulative p	Cumulative production		Peak oil production		Total number of wells		
Oil (bbl)	Net gas (Mcf)	Water (bbl)	acreage	producing wells	Oil (bbl)	Gas (Mcf)	Barrels	Year	Drilled	Completed	acreage
1,508,201	2,433,923	25,930,011	2,780	162	N.A.	N.A.	N.A.	N.A.	461	410	2,980

STIMULATION DATA (Jan. 1, 1974)

Type of project	Date started	Cumulative injection - Water, bbl; Gas, Mcf; Steam, bbl (water equivalent)	Maximum number of wells used for injection
Water flood	1954	120,032,572	70
Cyclic steam	1964	247,972	20

SPACING ACT: Does not apply

BASE OF FRESH WATER: 1,000

CURRENT CASING PROGRAM: 13 3/8" or 11 3/4" cem. 200 - 400; 8 5/8" or 7" cem. above zone and across base of fresh-water sands; 6 5/8" or 5 1/2" liner landed through zone; or 7" combination string landed through zone and cemented through ports above zone and across base of fresh-water sands.

METHOD OF WASTE DISPOSAL: Waste water is injected into water-disposal wells or is used in water-flood projects.

REMARKS:

REFERENCES: Huey, W.F., West Cat Canyon Area of Cat Canyon Oil Field: Calif. Div. of Oil and Gas, Summary of Operations--Calif. Oil Fields, Vol. 40, No. 1 (1954).

Manlove, C., West Cat Canyon Oil Field: Calif. State Div. of Mines Bull. 118, p. 432 (1938).

Prutzman, P.W., Petroleum in Southern California: Calif. State Mining Bureau Bull. 63, p. 382 (1912).

Regan, L.J. Jr., and A.W. Hughes, Fractured Reservoirs of Santa Maria District, California: Am. Assoc. Petroleum Geologists Bull., Vol. 33, No. 1, p. 32 (1949).

Woodring, W.P., and M.N. Bramlette, Geology and Paleontology of the Santa Maria District, California: U.S. Geol. Survey Prof. Paper 222, p. 120 (1950).